

UNLOADING EXACTLY WHERE NEEDED

Material Unloading Platform

**Is your storage space on the construction site too small?
Is the material too far from where it's needed on higher floors? Not anymore.
Material Loading Platforms allow you to deliver material exactly where you need it.**

Simple, fast, and safe

The loading platforms are available in three sizes and with three different enclosure variants. No matter which combination you choose, installation is straightforward, the platforms are quickly ready for use, and they can be easily dismantled for efficient transport.

www.peri.com



Three ways to unload material safely and quickly

The loading platforms consist of a platform support frame, an enclosure, and double doors at the front. They are designed to be easily installed between the floor and ceiling of any building level.

The only additional requirement for installation is two suitable supports with a minimum load capacity of 30 kN. The platforms can also be secured against slipping by bolting them to the ceiling.

After the quick and easy assembly of the loading platforms, they are immediately ready for use: Material can be loaded onto the platform either from outside by crane, from inside by hand or pallet truck, or from the ground floor using a pallet truck.



From narrow to wide: PERI platforms are available in three versions. There are three possible enclosures for each version.



The platform is located at board level.



Safety points for attaching personal protective equipment.



Eyelets for easy transport.



Non-slip floor.



Width: 1.27 m | 1.51 m | 2.20 m

Length: 3.50 m

Area: 4.45 m² | 5.29 m² | 7.70 m²

Weight (narrow): 745–821 kg

Weight (medium): 782–859 kg

Weight (wide): 929–1018 kg

Load capacity: up to 4 t

Support options with PERI supports:
PEP 30-350
PEP Ergo E-400